



Unit shown with service panels removed. Representative photo only. Some models may vary in appearance. Duct opening dimensions can be ascertained by subtracting 1-1/2" for top opening width/depth, 3/4" for bottom opening.



For complete warranty details  
visit [www.AspenMfg.com](http://www.AspenMfg.com)

### Product Features and Specifications

- Designed for use with R-454B and R-32 refrigerants
- Rifled aluminum tubing, enhanced aluminum fins
- Multi-stage leak testing with high-pressure testing at 500 psi, mass spectrometer pressure decay with helium, then sealed and nitrogen pressurized
- Left- or right-hand refrigerant and plumbing connections
- Heavy-duty plastic drain pans
- Embossed galvanized steel cabinets standard with painted options to OEM color
- Upflow standard; downflow with field-installed kit, sold separately.
- Split access doors in front of cabinet for easy service access
- Cabinets fully-insulated with foil faced insulation
- AHRI certifiable with all brands of AC and HP systems
- ETL listed for use with R-22, R-410A, R-454B, and R-32 when proper metering device is used
- Ten-year limited warranty with registration

### CUSTOMIZATION

- Factory or field installable TXV
- OEM color-matched cabinets
- High-temperature plastic drain pans

COIL MODEL	Nominal Capacity (BTUs)	R410-A PISTON SIZE	DIMENSIONS				SHIPPING INFORMATION			
			CABINET WIDTH		CABINET DEPTH	CABINET HEIGHT	SHIPPING WEIGHT (LBS)			SKID QTY
			MIN WIDTH	MAX WIDTH			2 ROW	3 ROW	4 ROW	
DC25A*	24,000	0.055	14	21	21-1/2	16	25	28	33	20
DC25B*		0.055	14	21	21-1/2	16	28	28	37	20
DC25C*		0.055	14	21	21-1/2	20	32	28	42	16
DC25D*		0.055	14	21	21-1/2	20	36	28	48	16
DC25E*		0.055	14	21	21-1/2	24	41	28	49	12
DC31A*	30,000	0.059	14	21	21-1/2	16	28	28	37	20
DC31B*		0.059	14	21	21-1/2	20	32	28	42	16
DC31C*		0.059	14	21	21-1/2	20	36	28	48	16
DC31D*		0.059	14	21	21-1/2	24	41	28	49	12
DC31E*		0.059	14	21	21-1/2	24	45	28	53	12
DC37A*	36,000	0.068	14	21	21-1/2	20	32	28	42	16
DC37B*		0.068	14	21	21-1/2	20	36	28	48	16
DC37C*		0.068	14	21	21-1/2	24	41	28	49	12
DC37D*		0.068	14	21	21-1/2	24	45	28	53	12
DC37E*		0.068	14	21	21-1/2	28	46	28	63	12
DC43A*	42,000	0.074	17	24-1/2	21-1/2	20	36	28	48	16
DC43B*		0.074	17	24-1/2	21-1/2	24	41	28	49	12
DC43C*		0.074	17	24-1/2	21-1/2	24	45	28	53	12
DC43D*		0.074	17	24-1/2	21-1/2	28	46	28	63	12
DC43E*		0.074	17	24-1/2	21-1/2	28	50	28	67	12
DC49A*	48,000	0.080	17	24-1/2	21-1/2	24	41	28	49	12
DC49B*		0.080	17	24-1/2	21-1/2	24	45	28	53	12
DC49C*		0.080	17	24-1/2	21-1/2	28	46	28	63	12
DC49D*		0.080	17	24-1/2	21-1/2	28	50	28	67	12
DC49E*		0.080	17	24-1/2	21-1/2	32	56	28	77	12
DC61A*	60,000	0.089	21	24-1/2	21-1/2	28	46	28	63	12
DC61B*		0.089	21	24-1/2	21-1/2	28	50	28	67	12
DC61C*		0.089	21	24-1/2	21-1/2	32	53	28	72	12
DC61D*		0.089	21	24-1/2	21-1/2	32	56	28	77	12

\*Notes: 1) do not use plastic drain pans on oil furnaces or other applications where outlet temperatures may exceed 290°F. Specialty metal drain pans are used for these applications. 2) For all coils- Liquid line 3/8" ODS; suction line 1/4" ODS for DC 25-37, 3/8" for DC 43-61.

Revised 2-24.

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.  
©2024